

TMT LEDs USA LLC
Irving, Texas 75063 USA
info@tmtledsusa.com
www.tmtledsusa.com

## Datasheet Game Changer TDS-Midi 4

Applications
Channel Letters
Lightboxes Cabinets
Cove Lighting













# Midi 4 LED Module



The all new, revolutionary TMT Game Changer Platinum Midi 4 module has efficiency at the center of its design. The CrystaLens optics provide a 170° viewing angle that dramatically reduces the number of modules required to provide bright, even illumination without hotspots. The incredibly efficient circuit design at the core of this powerful module outperforms every other module in the industry. Three times fewer modules delivers the same amount of brightness while reducing the power need by 30% making it the perfect product for large channel letters, sign cabinets and retrofitting existing fluorescent lighting.

#### **Features**

Best optical light dispersion in the industry
Unbeatable 240 – 320 lumens per module
Perfect for large channel letters and sign cabinets
when installed 3" - 10" from the face
Cable Hiding Technology (Patent Pending)
Efficient Circuit Design (Patent Pending)
Clean White Technology
Snap-in compatible to TMT LEDs aluminum
Midi Stick (Patent Pending)
Available in 12 and 24 volt formats
Up to 155 lumens per watt

### **Applications**

Ideal for large channel letters
with depths of 3" – 6"

Perfect for sign cabinets with installation depths of 2" to 10" from sign face



## TMT LEDs USA LLC Irving, Texas 75063 USA info@tmtledsusa.com www.tmtledsusa.com



Applications
Channel Letters
Lightboxes Cabinets
Cove Lighting

Operating Temperature -40°F ~ +140°F Lead Wire Tin Coated Copper Wire

Storage Temperature -40°F ~ +140°F Lifetime TM21 >60.000 Hours

Body Material Case: ABS | Optics: Optical PC Adhesive Tape 3M Foam

Finishing Ultrasonic Welding Strip Size 50 Modules/Strip

12V / 24 DC 3 SDCM 170° BEAM ANGLE

	Midi 4 12V	Midi 4 12V	Midi 4 24V
Power	1.7W	- • •2W • • •	• • 2W • •
Modules per foot	1 1 1 1	1 1 1	1 1
Kelvin	6500K	6500K	6500K
Voltage	12V	12V	24V
Lumen	250	300	300
Lumen/W	155	150	• • 150 • •
60W Power Supply Loading	32	27 • • •	• • • 27 • •
Order Code	105729	105919	105813



Luminous flux tolerance ±10% - CCT tolerance ±8%

